Mallory Sonalert Products, Inc.				Part #: JT120-RYG-CS	
Sales Outline Drawing				Revision: <b>B</b>	
Specifications:					
Stack Number:	1	2	3		
LED Color:	RED	YELLOW	GREEN		
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown		
LED Current Draw:	<210mA	<230mA	<190mA		
Rated Voltage:			120 VAC		
Operating Voltage:	90-120 VAC				
Total Max Current:	<630mA				
Operating Temperature:	-25° ~ +60°C				
Lens Color:	Opaque White				
Material:	ABS FR15U				
Mounting Method:	Stainless Steel Pole				
Weight Typical (g):	625				
NEMA 12:	Approved				
Options:	Please contact factory.				
Dimensions: Inches	s (mm)	cUL Recognized	I		ROHS Compliant
2.7 [68.3]— TDP VIEW	2.4 [61.8]		- - -	GASKET  Ø0.20 [Ø5.2] 3 places  10 or 5mm  Inews for mounting  0.39 [9.9]  0.95 [24.3]  MDUNTING  DIAGRAM	48* wire for wires 2.04 [51.9] 0.95 [24.3]
LED OPERATION:  CONN	IECT STACK COL	OR WIRE TO POWER F	AND BROWN WIRE	TO POWER.	